



**AFRL-RH-WP-TP-2012-0006**

**SELECTED VAPOR PHASE SENSING OF SMALL MOLECULES  
USING BIOFUNCTIONALIZED FIELD EFFECT TRANSISTORS**

Joshua A. Hagen, Nancy Kelley-Loughnane, Morley O. Stone

**Forecasting Division  
Human Signature Branch**

Sang Nyon Kim, Rajesh R. Naik

**Non Metallic Materials  
Nanostructured and Biological Materials**

**FEBRUARY 2012  
Interim Report**

**Distribution A: Approved for public release; distribution is unlimited.**

*See additional restrictions described on inside pages*

**AIR FORCE RESEARCH LABORATORY  
711<sup>TH</sup> HUMAN PERFORMANCE WING,  
HUMAN EFFECTIVENESS DIRECTORATE,  
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433  
AIR FORCE MATERIEL COMMAND  
UNITED STATES AIR FORCE**

## NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report was cleared for public release by the 88<sup>th</sup> Air Base Wing Public Affairs Office and is available to the general public, including foreign nationals. Copies may be obtained from the Defense Technical Information Center (DTIC) (<http://www.dtic.mil>).

AFRL-RH-WP-TP-2012-0006 HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH ASSIGNED DISTRIBUTION STATEMENT.

//signature//  
NANCY KELLEY-LOUGHNANE  
Work Unit Manager  
Human Signature Branch

//signature//  
LOUISE A. CARTER, PhD  
Forecasting Division  
Human Effectiveness Directorate  
711<sup>th</sup> Human Performance Wing  
Air Force Research Laboratory

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings.

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. <b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p>					
1. REPORT DATE (DD-MM-YY) 01 FEB 12		2. REPORT TYPE Interim		3. DATES COVERED (From - To) 26 JAN 2010- 26 JAN 2012	
4. TITLE AND SUBTITLE SELECTIVE VAPOR PHASE SENSING OF SMALL MOLECULES USING BIOFUNCTIONALIZED FIELD EFFECT TRANSISTORS				5a. CONTRACT NUMBER In-House	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 62202F	
6. AUTHOR(S) *Joshua A. Hagen, Nancy Kelley-Loughnane, Morley O. Stone **Sang Nyon Kim, Rajesh R. Naik				5d. PROJECT NUMBER 7184	
				5e. TASK NUMBER C	
				5f. WORK UNIT NUMBER 7184C001	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ** AFRL Materials and Manufacturing Directorate 3005 Hobson Way, B652 Wright-Patterson Air Force Base, OH 45433				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) *Air Force Materiel Command Air Force Research Laboratory 711 <sup>th</sup> Human Performance Wing Human Effectiveness Directorate Forecasting Division Human Signature Branch Wright-Patterson Air Force Base, OH 45433				10. SPONSORING/MONITORING AGENCY ACRONYM(S) 711 HPW/RHXB	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER(S) AFRL-RH-WP-TP-2012-0006	
12. DISTRIBUTION/AVAILABILITY STATEMENT Distribution A: Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES 88ABW cleared on 7 Jun 2011, 88ABW-2011-3250					
14. ABSTRACT This work details a proof of concept study for vapor phase selective sensing using a strategy of biorecognition elements (BRE) integrated into a zinc oxide field effect transistor (ZnO FET). ZnO FETs are highly sensitive to changes to the environment with little to no selectivity. Addition of a biorecognition element retains the sensitivity of the device while adding selectivity. The DNA aptamer designed to bind the small molecule riboflavin was covalently integrated into the ZnO FET and detects the presence of 116 ppb of riboflavin in a nitrogen atmosphere by a change in current. The unfunctionalized ZnO FET shows no response to this same concentrations of riboflavin, showing that the aptamer-binding strategy may be a promising strategy for vapor phase sensing.					
15. SUBJECT TERMS DNA aptamer, biological recognition element, field effect transistor, sensor, zinc oxide, riboflavin					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT: SAR	18. NUMBER OF PAGES 15	19a. NAME OF RESPONSIBLE PERSON (Monitor) Nancy Kelley-Loughnane 19b. TELEPHONE NUMBER (Include Area Code) N/A
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			

**THIS PAGE IS INTENTIONALLY LEFT BLANK**

## TABLE OF CONTENTS

<b>ABSTRACT.....</b>	<b>1</b>
<b>1. INTRODUCTION .....</b>	<b>1</b>
<b>2. EXPERIMENTAL.....</b>	<b>2</b>
2.1 Device geometry and experimental setup .....	2
2.2 Device testing – Bias stressing.....	3
2.3 Non-selective vapor testing.....	3
2.4 Selective vapor testing – exposure to riboflavin .....	5
<b>3. CONCLUSIONS .....</b>	<b>7</b>
<b>REFERENCES.....</b>	<b>8</b>

## LIST OF FIGURES

Figure 1. ZnO AptafET .....	2
Figure 2. Source/Drain Current (A) versus Time: Bias stressing study of ZnO AptafET with $V_{SD} = 5V$ .....	3
Figure 3. Source/Drain current (A) versus Time with varying nitrogen flowrates .....	4
Figure 4. Source/Drain Current (A) versus Time (s) for exposure of the ZnO FET to a) ethanol and b) acetone .....	5
Figure 5. Source/Drain Current (A) versus Time (s) for an unfunctionalized ZnO FET and exposed to 116 ppb riboflavin vapor in nitrogen .....	6
Figure 6. Source/Drain Current (A) versus Time (s) for a riboflavin-Aptamer functionalized ZnO FET and exposed to 116 ppb riboflavin vapor in nitrogen .....	7

**THIS PAGE IS INTENTIONALLY LEFT BLANK**

# Selective vapor phase sensing of small molecules using biofunctionalized field effect transistors

Joshua A. Hagen<sup>\*a</sup>, Sang Nyon Kim<sup>b</sup>, Nancy Kelley-Loughnane<sup>a</sup>, Rajesh R. Naik<sup>b</sup>, Morley O. Stone<sup>a</sup>

<sup>a</sup>Air Force Research Laboratory, Human Effectiveness Directorate, 2729 R St., Wright Patterson AFB, OH 45433-5707

<sup>b</sup>AFRL Materials and Manufacturing Directorate

## ABSTRACT

This work details a proof of concept study for vapor phase selective sensing using a strategy of biorecognition elements (BRE) integrated into a zinc oxide field effect transistor (ZnO FET). ZnO FETs are highly sensitive to changes to the environment with little to no selectivity. Addition of a biorecognition element retains the sensitivity of the device while adding selectivity. The DNA aptamer designed to bind the small molecule riboflavin was covalently integrated into the ZnO FET and detects the presence of 116 ppb of riboflavin in a nitrogen atmosphere by a change in current. The unfunctionalized ZnO FET shows no response to this same concentrations of riboflavin, showing that the aptamer-binding strategy may be a promising strategy for vapor phase sensing.

**Keywords:** DNA aptamer, biological recognition element, field effect transistor, sensor, zinc oxide, riboflavin

## 1. INTRODUCTION

Development of sensor elements and devices requires the ability to determine the presence and concentration of target molecules of interest. A number of strategies are used to achieve this, such as mass spectrometry<sup>1,2</sup>, biomolecular interaction analysis (BIA)<sup>3,4,5</sup>, and mass based resonance sensing<sup>6,7</sup>. Recent advances in sensor development highlight a selective sensing strategy using biorecognition elements (BRE)<sup>8</sup>, such as DNA/RNA aptamers<sup>9,10</sup> or peptides<sup>11,12</sup>. Instead of using complex separations or algorithms for data interpretation, the BRE offers a point based detection where the specific molecule of interest is bound directly by the BRE. The binding event can then be transduced into a reportable signal based on the sensor platform in which it is integrated. A number of different sensing platforms have been developed with BRE integration such as electronic<sup>13</sup>, optical<sup>14,15</sup>, and mechanical devices<sup>16</sup>. One of the more promising platforms is the biofunctionalized field effect transistor (BioFET). The semiconductor in the FET is particularly sensitive to surface effects or changes, with little to no selectivity. These surface changes can be due to environmental effects such as the presence of liquids or vapors. Attaching a BRE to the semiconductor adds selectivity while maintaining the inherent sensitivity of the surface and has been successfully shown on various semiconductors such as carbon nanotubes<sup>12,17</sup>, silicon nanowires<sup>18</sup>, and zinc oxide<sup>19</sup>. However, a majority of the work with BRE-FETs is in the liquid sensing environment.

Previous work in this group involved using a zinc oxide (ZnO) FET with an integrated DNA aptamer that was selected for the small molecule riboflavin<sup>19</sup>. Selective detection was achieved below nano-molar levels in the liquid phase. The work presented here describes the initial studies

on the feasibility to detect riboflavin in the vapor state using the same ZnO aptamer-FET (AptaFET) strategy.

## 2. EXPERIMENTAL

### 2.1 Device geometry and experimental setup

The ZnO FETs were designed for ease of handling and testing while maintaining the active area presented in previous work. The interdigitated electrode distance is 10  $\mu\text{m}$  and has extended contact pads (400  $\mu\text{m}^2$ ). Three sets of three FETs were fabricated on a diced chip which is 20 mm x 7.5 mm as shown in Figure 1 below. The devices were fabricated in a 3 mask design on a 3" silicon wafer. The first mask was used for patterning thick  $\text{SiO}_2$  insulator paths along the extended contact lines, the second for patterning the ZnO only in the active area (green region in Figure 1a right), and third for the top electrode patterning. The ZnO was deposited using pulsed laser deposition described previously<sup>20</sup>. The dry state device performance shows an excellent on/off ratio of  $10^6$  (A) shown in Figure 1b.

The next step is attaching the DNA aptamer, which is functionalized with a thiol group as specified and purchased from IDT Technologies. The sequence and structure of the riboflavin binding aptamer is well known<sup>21</sup>, and is used in these experiments as: 5'-Thiol-AGAGAGGAACGACGGTGGTGGAGGAGATCGTTCC-3'. The thiol group on the aptamer provides the linkage to the ZnO via a silane linker as described previously<sup>19</sup>. The surface morphology of a covalently attached aptamer on ZnO is shown in the micrograph in Figure 1c.




Figure 1. ZnO AptaFET

*a) Schematic of device geometry with full chip image on the left, zoom in of single set of FETs in center, and individual FET right, b) Dry state device performance, c) Atomic force micrograph of aptamer functionalized ZnO semiconductor*



## 2.2 Device testing – Bias stressing

Initial testing of the devices in a nitrogen atmosphere showed a significant downward drift of current when a constant voltage ( $V_G = 5V$ ,  $V_{SD} = 0.2V$ ) was applied. A bias stressing study was done based on work by Marks et al.<sup>22</sup> to reduce this drift and have a steady starting current. Bias stressing is done by applying a large voltage (5V) to the source/drain electrodes to help clear any charges that are trapped between the insulator and semiconductor layers. This can be done in cycles, and is complete once a steady charge state is achieved. A bias stressing study is shown in Figure 2 below, where 5V was applied for 500 seconds in 5 cycles. An additional 6<sup>th</sup> cycle was tested after the device sat in the nitrogen environment for 2 hours. Even after the 2 hour delay, the bias stressing remained effective with a largely decreased drift.




Figure 2. Source/Drain Current (A) versus Time: Bias stressing study of ZnO AptafET with  $V_{SD} = 5V$

## 2.3 Non-selective vapor testing

For baseline performance testing, the unfunctionalized ZnO FET was evaluated in a nitrogen atmosphere as well as adding additional vapors to the nitrogen stream. The first evaluation was the effect of nitrogen flowrate on the device. Figure 3 below shows that varying the nitrogen flowrate from 50 to 100 mL/min had no effect on the current flowing through the FET.




Figure 3. Source/Drain current (A) versus Time with varying nitrogen flowrates

As mentioned previously, unfunctionalized FETs commonly respond to a wide variety of vapors. Many vapor molecules non-selectively interact with the surface causing the current to modulate. The fact that the devices can respond to a variety of vapors is promising, but again there is no selectivity. These interactions are shown in Figure 4 below, where high concentrations of ethanol and acetone were exposed to the unfunctionalized ZnO FET. The vapors were generated by bubbling nitrogen through the liquids. Figure 4a shows high concentration exposure of ethanol, and 4b acetone. In both cases, the current is significantly increased upon exposure. In the case of ethanol, the vapor seems to desorb as the current decreases and approaches the initial level. Acetone does not appear to desorb where a constant elevated current is maintained.




Figure 4. Source/Drain Current (A) versus Time (s) for exposure of the ZnO FET to a) ethanol and b) acetone

## 2.4 Selective vapor testing – exposure to riboflavin

The negative aspect of using surface sensitive FETs in vapor sensing applications is the lack of selectivity upon exposure to various vapors. This can be partially overcome by incorporating selective recognition elements, such as the riboflavin DNA aptamer, which was evaluated upon exposure to riboflavin vapor. Since riboflavin is a solid with very low vapor pressure, an Owlstone vapor generator was used to create the vapor stream. Riboflavin was placed in a permeable tube and inserted into the oven of the vapor generator. A constant nitrogen flowrate (50 mL/min) was flowed through the oven, and a calibration curve was established to determine the amount of riboflavin that was vaporized. This corresponded to a riboflavin vapor flowrate of 116 ppb (309 nM) in 50 mL/min of nitrogen. A negative control experiment was run which included exposure of a non functionalized ZnO FET exposed to 116 ppb riboflavin, and is shown in Figure 5. A constant nitrogen flow with and without riboflavin vapor was cycled back and forth to establish whether any recognition was evident.

Upon functionalization of the ZnO FET with the riboflavin aptamer, detection of riboflavin in the vapor phase is possible, shown in Figure 6. When riboflavin is introduced into the nitrogen stream, the current quickly begins to decrease, which corresponds to the mechanism described previously<sup>19</sup>. After the riboflavin flow is stopped (while maintaining nitrogen flow), the current continues to decrease, likely due to the slow absorption transport to the surface and residual riboflavin in the chamber which has not been cleared. After purging with nitrogen, the riboflavin appears to desorb from the surface shown by the increase in current at ~1200 s. Additional cycles between pure nitrogen and riboflavin vapor shows continued detection of riboflavin that is not seen in the unfunctionalized device.




Figure 5. Source/Drain Current (A) versus Time (s) for an unfunctionalized ZnO FET and exposed to 116 ppb riboflavin vapor in nitrogen




Figure 6. Source/Drain Current (A) versus Time (s) for a riboflavin-Aptamer functionalized ZnO FET and exposed to 116 ppb riboflavin vapor in nitrogen

### 3. CONCLUSIONS

Field effect transistor sensors can be incorporated into standard integrated electronic systems which can rapidly transmit sensing data to a computer, handheld sensor, or even wirelessly. A great deal of research has been, and is currently being pursued for liquid phase FET sensor systems with added selectivity provided by biorecognition elements. The preliminary data established here shows a promising route for selective sensing in the vapor phase. By incorporating the riboflavin binding aptamer to a ZnO FET, we show that riboflavin can be detected at ppb levels in the vapor phase. No detection occurs with an unfunctionalized ZnO FET.

The next steps in this research include testing of additional targets using both aptamers and peptides, testing these in more complex vapor environments, and coupling with microchannel technologies for increased surface exposure to the vapors.

## REFERENCES

- <sup>1</sup> Naik, A.K., Hanay, M.S., Hiebert, W.K., Feng, X.L., Roukes, M.L., "Towards single-molecule nanomechanical mass spectrometry," *Nature Nanotechnology* 4, 445-450 (2009).
- <sup>2</sup> Gilligan, J.J., Schuck, P., Yergey, A.L., "Mass Spectrometry after Capture and Small-Volume Elution of Analyte from a Surface Plasmon Resonance Biosensor," *Anal. Chem* 74 (9), 2041-2047 (2002).
- <sup>3</sup> Krone, J.R., Nelson, R.W., Dogruel, D., Williams, P., Granzon, R., "BIA/MS: Interfacing Biomolecular Interaction Analysis with Mass Spectrometry," *Anal. Biochem.* 244, 1, 124-132 (1997).
- <sup>4</sup> Nedelkov, D., Nelson, R.W., "Surface plasmon resonance mass spectrometry: recent progress and outlooks," *Trends in Biotechnology*, 21, 7, 301-305 (2003)
- <sup>5</sup> Rich, R.L., Myszka, D.G., "Advances in surface plasmon resonance biosensor analysis," *Current Opinion in Biotechnology*, 11, 54-61 (2000).
- <sup>6</sup> Caruso, F., Rodda, E., Furlong, D.N., "Quartz Crystal Microbalance Study of DNA Immobilization and Hybridization for Nucleic Acid Sensor Development," *Anal. Chem.* 69, 11, 2043-2049 (1997)
- <sup>7</sup> Jensen, K., Kim, K., Zettl, A., "An atomic-resolution nanomechanical mass sensor," *Nature Nanotechnology*, 3, 533-537 (2008)
- <sup>8</sup> Willner, I., "Biomaterials for sensors, fuel cells, and circuitry," *Science* 20 (298), 2407-2408 (2002).
- <sup>9</sup> Xiao, Y., Lubin, A., Heeger, A., Plaxco, K., "Label-Free Electronic Detection of Thrombin in Blood Serum by Using an Aptamer-Based Sensor," *Angew. Chemie*, 117, 34, 5592-5595 (2005)
- <sup>10</sup> O'Sullivan, C.K., "Aptasensors –the future of biosensing?" *Anal. Bioanal. Chem.* 372, 1, 44-48 (2002).
- <sup>11</sup> Peczu, M.W., Hamilton, A.D., "Peptide and Protein Recognition by Designed Molecules," *Chem. Rev.*, 100, 7, 2479-2494 (2000).
- <sup>12</sup> Kuang, Z., Kim, S.N., Crookes-Goodson, W.J., Farmer, B.L., Naik, R.R., "Biomimetic Chemosensor: Designing Peptide Recognition Elements for Surface Functionalization of Carbon Nanotube Field Effect Transistors," *ACS Nano*, 4, 1, 452-458 (2010).
- <sup>13</sup> Willner, I., Zayats, M., "Electronic Aptamer-Based Sensors," *Angew. Chemie*, 46, 34, 6408-6418 (2007).
- <sup>14</sup> Stojanovic, M.N., Landry, D.W., "Aptamer-Based Colorimetric Probe for Cocaine," *J. Am. Chem. Soc.* 124, 33, 9678-9679 (2002).
- <sup>15</sup> Chavez, J.L., Lyon, W.J., Kelley-Loughnane, N.K., Stone, M.O., "Theophylline detection using an aptamer and DNA-gold nanoparticle conjugates," *Biosensors Bioelectronics*, 26, 1, 23-28 (2010).
- <sup>16</sup> Savran, C.A., Knudsen, S.M., Ellington, A.D., Manalis, S.R., "Micromechanical Detection of Proteins Using Aptamer-Based Receptor Molecules," *Anal. Chem.*, 76, 11, 3194-3198 (2004).
- <sup>17</sup> Allen, B.L., Kichambare, P.D., Star, A., "Carbon Nanotube Field-Effect-Transistor-Based Biosensors," *Adv. Mat.* 19, 11, 1439-1451 (2007).
- <sup>18</sup> Cui, Y., Wei, Q., Park, H., Lieber, C. "Highly sensitive and selective detection of biological and chemical species," *Science* 293, 1289-1292 (2001).
- <sup>19</sup> Hagen, J.A., Kim, S.N., Bayraktaroglu, B., Kelley-Loughnane N.K., Naik, R., Stone, M.O., "DNA aptamer functionalized zinc oxide field effect transistors for liquid state selective sensing of small molecules," *Proc SPIE Vol.* 7759 (2010).

---

<sup>20</sup> Bayraktaroglu, B., Leedy, K., Neidhard, R., “High-frequency ZnO thin-film transistors on Si substrates,” IEEE Electron Device Letters 30 (9), 946-948 (2009).

<sup>21</sup> Lauhon, C., Szostak, J., “RNA aptamers that bind flavin and nicotinamide redox cofactors,” J. Am. Chem. Soc. 117, 1246-1257 (1995).

<sup>22</sup> Ju, S., Janes, D.B., Lu, G., Facchetti, A., Marks, T.J., “Effects of bias stress on ZnO nanowire field-effect transistors fabricated with organic gate nanodielectrics,” Appl. Phys. Lett. 89, 193506 (2006).